Pump Model	Pump Rating		Pipe Size (mm)		TOTAL HEAD IN METRES															Rated			
					6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	40		Voltag (Volta
	KW	HP	SUC.	DEL.						C	APAC	ITY I	N LITI	RES F	PER S	ECOI	ND						Ċ.
KDS-216++	1.5	2.0	65	50		11.0	10.0	8.8	7.15	4.0										2			415
KDS-225++	1.5	2.0	50	40		5.3	5.18	4.9	4.75	4.5	4.25	3.9	3.56	3.1	2.25								415
KDS-235++	1.5	2.0	50	40			4.1	4.0	3.4	3.8	3.6	3.4	3.1	2.8	2.6	2.4	2.0	1.5	1.1				415
KDS-314+	2.2	3.0	80	80	19.1	17.8	16.2	13.8	10.4														41
KDS-318++	2.2	3.0	80	65		13.4	12.6	11.7	10.7	9.2	7.5												41
KDS-325++	2.2	3.0	65	50			9.2	8.8	8.4	7.9	7.4	7.0	6.4	5.8	4.9								41
KDS-335++	2.2	3.0	50	40				5.0	4.9	4.8	4.7	4.6	4.4	4.2	4.0	3.8	3.6	3.2	2.7	2.0			41
KDS-515+	3.7	5.0	100	100	32.8	31.0	28.0	24.2	19.0	12.9													40
KDS-520+	3.7	5.0	80	80	24.0	23.0	22.0	20.8	19.5	17.9	16.0	14.0	11.0										40
KDS-527++	3.7	5.0	80	65						14.3	13.5	12.5	11.6	10.3	8.7	6.4							40
KDS-822++	5.5	7.5	100	100				27.3	25.6	24.0	22.2	20.1	17.6	14.5									40
KDS-830++	5.5	7.5	80	65						19.0	18.2	17.3	16.4	15.4	14.2	13.0	11.1						40
KDS-1030++	7.5	10.0	100	100				32.0	31.0	29.8	28.5	27.0	25.0	23.5	21.0	18.0							41
KDS-1040+	7.5	10.0	80	65			23.5	23.0	22.6	22.2	21.6	20.9	20.35	19.5	18.75	17.9	17.0	15.7	14.6	13.4	9.6		41
					18	20	24	28	30	32	36	40	44	48	52	54	56	60	64	68	72	76	
KDS-538+	3.7	5.0	65	50		8.5	8.3	7.8	7.6	7.1	5.8												40
KDS-550++	3.7	5.0	50	40							4.1	3.7	3.3	2.7	2.0								40
KDS-837	5.5	7.5	65	65				12.6	12.2	11.8	11.1	9.0									1		40
KDS-844++	5.5	7.5	65	65			10.7	10.3	9.9	9.5	8.4	7.1	4.7										40
KDS-852++	5.5	7.5	65	50						8.6	8.1	7.5	6.8	5.9	4.5	3.7							40
KDS-1050++	7.5	10.0	65	65			12.9	12.5	12.3	12.0	11.4	10.7	9.6	8.1	6.0								41
KDS-1065++	7.5	10.0	65	50								7.8	7.4	6.9	6.4	6.1	5.8	5.1	4.3	3.0			41
KDS-1331+	9.3	12.5	100	100	33.4	32.0	29.0	23.8	12.5														41
KDS-1348+	9.3	12.5	80	65		19.6	18.9	18.2	17.8	17.3	15.8	14.3	11.9										41
KDS-1360+	9.3	12.5	65	50	12.8	12.6	12.4	12.2	12.1	11.9	11.7	11.4	11.0	9.6	9.6	8.8	8.2						41
KDS-1537+	11.0	15.0	100	100	36.8	35.9	33.0	30.0	28.0	25.0	17.5												41
KDS-1555+	11.0	15.0	80	65					19.4	19.2	18.5	17.4	16.0	14.5	12.2	10.5							41
KDS-1570+	11.0	15.0	65	50					13.1	13.0	12.7	12.5	11.7	11.5	10.7	10.2	9.7	9.0	8.0	6.5			41
KDS-1575+	11.0	15.0	65	50											8.1	7.9	7.7	7.4	6.9	6.4	5.8	4.9	41
KDS-2030+	15.0	20.0	125	125	47	45	39	30	21												1		41
KDS-2050+	15.0	20.0	100	80	33.8	33.2	31.8	30.4	29.7	28.8	27.2	25.0	22.8	19.4									41
KDS-2560+	18.7	25.0	100	80										24.5	22.0	20.5	18.6	13.0					41
KDS-3068+	22.0	30.0	100	80										28.0	26.5	25.6	24.5	21.5	17.5	10.0			41

