Kirloskar 'KOS M' Series Single Phase Pumps

Single Stage, High Speed, Horizontal, Centrifugal, Openwell Submersible, Monobloc Pumps with Volute Type Delivery Casing

Range

Head

: 8-28 metres.

Capacity : 11-0.4 litres per second

Power Rating : 0.37 kW to 1.5 kW

(0.5 HP to 2.0 HP)

Material of Construction

Standard Supply

Impeller : Cast Iron
Delivery casing : Cast Iron
Motor body : Cast Iron
Shaft : Sainless Steel

Direction of Rotation

Anticlockwise, when viewed from suction side.

Optional Supply

Impeller : Bronze

Approximate Performance of 'KOS M'series, 2 pole, Openwell Submersible Monobloc Pumps at Rated Voltage, 50Hz, Single Phase, AC Power Supply:

PUMP MODEL	POV RAT		PIPE SIZE (mm)		TOTAL HEAD IN METRES											RATED
	kW	HP	SUC.	DEL.	8	10	12	14	16	18	20	22	24	26	28	VOLTAGE (VOLTS)
					CAPACITY IN LITRES PER SECOND											
KOS-0516M	0.37	0.5	25	25	1.8	1.6	1.4	1.0	0.6							210
KOS-116M	0.75	1.0	50	40	4.9	4.5	4.0	3.5	2.9	2.0						210
KOS-128M*	0.75	1.0	25	25			2.0	1.9	1.8	1.7	1.6	1.4	1.1	0.8	0.4	210
KOS-1.522M	1.1	1.5	50	40	6.3	5.9	5.5	5.0	4.5	3.8	3.0	1.9				210
KOS-1.525M	1.1	1.5	50	40					2.3	2.2	2.1	2.0	1.8	1.6	1.3	210
KOS-216M	1.5	2.0	65	50	11.0	10.0	8.8	7.2	4.0							210
KOS-225M	1.5	2.0	50	40	5.3	5.1	5.0	4.8	4.5	4.3	4.0	3.6	3.1	2.2		210

Note: Performance applicable to liquid of specific gravity 1 and viscosity as of water. All pumpsets except KOS-216M and KOS-225M are ISI marked. * KOS-128M can also be offered in (50x40) and (40x40) mm pipe size.



Enriching Lives

Openwell Submersible Pumps





KOS M-080200

Applications

vibrations.

spanner for maintenance.

• Water supply for fountains, sump and water tanks.

Replaceable wearing parts and hence longer life.

 Water supply for domestic use in apartments, buildings and hotels.

Non overloading power characteristics - No fear of motor

Dynamically balanced rotating parts ensure minimum

• Easy maintenance and spares availability - Needs only one

Gardening and small farm irrigation.